

## JME Holemaker III

Endurance magnetic base drill up to 1-3/8 [35] in[mm]

Order number:: 7 270 59 61 09 0



The optimal drilling solution with high powered German motor designed for use with Carbide and HSS cutters for toughest jobs and applications.

- Externely wear resistant concept with durable newly designed polyurthane motorhousing for use in industry and manual trades.
- Externely lightweight drill yet powerful enough for heaviest drilling applications.
- Cost effective drill for running with Carbide cutters which offer longer life, higher cutting rate and capable of cutting harder materials. Also running with standard HSS cutters with great results.
- Optimum power-to-weight ratio.
- Integrated cooling tank.
- Magnet holding power detection below 3/16 in [4] in[mm].
- Pivoting motor cable.
- Higher RPM for optimal use with carbide cutters.
- Side-reversible feed handwheel with hexagonal hub.
- Integrated hexagon socket holder.



## JME Holemaker III

Endurance magnetic base drill up to 1-3/8 [35] in[mm]

Order number:: 7 270 59 61 09 0

## Technical data

Dower consumption	1 100 Watta
Power consumption	1,100 Watts
Power output	510 Watts
Full load speed	450 rpm
Twist drill max. dia.	5/8 In
Mag base, max. drilling depth	2 In
Carbide annular cutter max. dia.	1-3/8 In
HSS annular cutters max. dia.	1-3/8 In
Annular cutter holder	3/4 in Weldon
Stroke	5-11/16 ln
Total stroke range	10-1/4 In
Magnetic holding force	2,810 lbs
Magnetic base dimensions	7-11/16 x 3-9/16 ln
Cable with plug	9 ft
Weight according to EPTA	25.8 lbs
Corded	Х

## Price includes:

1 coolant tank
1 safety strap
2 pilot pins
1 touch guard
2 hexagonal socket keys, 3/16 [5] and 1/4 [6] in[mm]
1 hexagonal socket keys with T-grip, 1/4 [5] in[mm]
1 case